



SS FLOW
A NEVER ENDING JOURNEY

SS Automation & Instrumentation Company

One stop Solution for all kind of Instrumentation & Electromechanical solution
Manufacturer & supply of process instruments & NABL Calibration & Validation Services

SSFLOW_DIFFERENTIAL PRESSURE TRANSMITTER



Features

- 316L stainless steel diaphragm structure
- Differential pressure measurement
- Easy to install
- Zero and full scale span adjustable externally
- Short circuit protection and reverse polarity protection
- Excellent shock resistance, vibration resistance and electromagnetic compatibility resistance
- Customization available

Applications

- Equipment support
- Scientific experiment
- Precision instrument
- Water supply and drainage
- Power plant differential pressure
- Flow

Product overview

PCM610 Differential Pressure Transmitter is assembled using an OEM piezoresistive silicon differential pressure sensor filled with oil. The shell is made of stainless steel and has strong corrosion resistance. The two pressure ports are threaded and can be mounted directly on the measuring pipe or connected through the pressure pipe. PCM610 series have standard voltage/current output options, which can be easily installed and used. The products are widely used in the measurement and control of differential pressure, liquid level and flow in process control, aviation, aerospace, automotive, medical equipment, HVAC, etc.

Notes:

- 1 Do not misuse documentation.
- 2 The information presented in this product sheet is for reference only. Do not use this document as a product installation guide.
- 3 Complete installation, operation, and maintenance information is provided in the instructions of the product.
- 4 Misuse of the product may cause danger or personal injury.



SS Automation & Instrumentation Company

One stop Solution for all kind of Instrumentation & Electromechanical solution

Manufacturer & supply of process instruments & NABL Calibration & Validation Services

Performance parameters

Pressure range	0~10kPa...2.5MPa
Static pressure	20MPa(Max.)
Pressure reference	Differential pressure
Supply & output	4~20mA(16~36VDC) 1~5V, 0~5V(12~36VDC)
Accuracy	0.5%FS(typ.)
Temp. drift	1.5%FS(@-10℃~70℃)
Response time	1ms(Up to 90%FS)
Service life	≥10×10 ⁶ pressure cycles
Ambient temp.	-10℃~70℃
Medium temp.	-10℃~70℃
Storage temp.	-40℃~125℃
EMC-interference	IEC 61000-6-3
EMC-immunity	IEC 61000-6-2
Insulation resistance	200MΩ/250VDC
Shock resistance	100g(11ms)
Protection	IP65
Material	304
Max. mounting torque	25Nm

Pressure range selection

Pressure range code	Pressure range	Positive overpressure	Negative overpressure	Remark
10k	0~10kPa	300%FS	300%FS	
20k	0~20kPa	300%FS	300%FS	
35k	0~35kPa	300%FS	300%FS	
70k	0~70kPa	300%FS	300%FS	
100k	0~100kPa	300%FS	300%FS	
200k	0~200kPa	300%FS	300%FS	
250k	0~250kPa	200%FS	200%FS	
500k	0~500kPa	200%FS	200%FS	
0.6M	0~0.6MPa	200%FS	200%FS	
1M	0~1MPa	200%FS	150%FS	
1.6M	0~1.6MPa	200%FS	150%FS	
2.5M	0~2.5MPa	200%FS	150%FS	